

Mounts for High Frequency Antennas

High frequency mounts designed for our mobile high frequency antennas, including:

		
<p>MEFC49005HF Elevated feed model covering frequencies of 4.9-5.0 GHz with 5 dBi gain.</p>	<p>MEFC58005HF Elevated feed model covering frequencies of 5.7-5.8 GHz with 5.5 dBi gain.</p>	<p>MLPV4900NGP Low profile vertical antenna covering frequencies of 4.9-5.0 GHz with 3 dBi gain. No ground plane required.</p>

High Frequency Mounts for Thick Roof Surfaces

5/8" hole; 1-1/8"-18 thread; Crimp on

Model	Mount Type	Coax	Connector
NEW! MVPHF	Vandal-proof microwave mount for frequencies from 3.0 GHz to 5.8 GHz. For surfaces up to 1/2-inch thick.	None	M to N female connector
MTPMHF	Permanent microwave mount for frequencies from 3.0 GHz to 5.8 GHz. For surfaces up to 1-inch thick.	None	N female connector



MVPHF



MTPMHF

High Frequency Mounts

3/4" hole; 1-1/8"-18 thread; Crimp on

Model	Mount Type	Coax	Connector
NEW! MHFPP240C	Permanent microwave mount for frequencies from 3.0 to 5.8 GHz	17 ft. Pro-Flex™ Plus 240	Loose TNC male standard. Contact factory for other connector options.
NEW! GMHFP240C	Permanent microwave mount for frequencies from 3.0 to 5.8 GHz	12 ft. Pro-Flex™ Plus 240	Loose TNC male standard. Contact factory for other connector options.
MHFML195C	Permanent microwave mount for frequencies from 3.0 GHz to 5.8 GHz	17 ft. Pro-Flex™ Plus 195	Loose TNC male standard. Contact factory for other connector options.
GMHFML195C	Magnetic base microwave mount for frequencies from 3.0 GHz to 5.8 GHz	12 ft. Pro-Flex™ Plus 195	Attached TNC male standard. Contact factory for other connector options.



MHFPP240C



MHFML195C



GMHFML195C