



3.3 to 3.8 GHz Parabolic Reflector Antenna Series with Radome

The MPRC prime focus parabolic reflector antenna series suppresses extraneous sidelobe and cross-polarized energy. These antennas feature a micro fine elevation and azimuth adjustment kit. The MPRC series is provided with a radome as a standard feature.

Features

- Availability in two and three foot diameter sizes
- Radome comes standard and installed
- Rear mounted feed - radome never has to be removed
- Continuous polarization adjustment
- Fine adjustment mechanism for elevation and azimuth
- Assembled and attached offset mount allows easy access to connector
- Double saddle mounting brackets will accommodate pipe attachments ranging from 1.625" to 4.5" OD
- Robust mounting structure. Three point mount attachment improves stability and prevents reflector distortion and mechanical oscillation
- 2 foot versions are UPS shippable



Technical Data

General Specifications: Prime Focus Parabolic Reflector Antenna
Maximum Power: 5 watts
Nominal Impedance: 50 ohms
SWR/return loss: < 1.5 / >13.9 dB
Polarization: Linear, continuously adjustable
Front-to-back Ratio: 32 dB (MPRC2434) 33 dB (MPRC3634)
Interface Connector: Type N female
Mount Interface: Accommodates 1.625" to 4.5" OD

Antenna Electrical Specifications

Model	Frequency Range	Nominal Gain (+/- 0.5 dB at mid band)	3 dB Beamwidth, Nominal
MPRC2434	3.3 - 3.8 GHz	25.0 dBi	8.7°
MPRC3634	3.3 - 3.8 GHz	27.8 dBi	6.3°

Mechanical Specifications

Model	Wind Survival with 1/2" of radial ice	Temperature Range	Diameter
MPRC2434	125 mph	-40°C to +80°C	26"
MPRC3634	125 mph	-40°C to +80°C	36"